



W= Width, D= Depth, H=Height

230V ~ 50Hz



DEFA Termini™ 1350

DEFA Termini™ 1350 utilise a PTC heating element (PTC = Positive Temperature Coefficient). As the interior temperature rises, power output is reduced and thus power consumption as well.

The interior heater is equipped with an automatic overheating circuit breaker. This breaker is tripped at 55°C, and it is reset by disconnecting the plug and leaving the interior heater switched off until it cools down (after approx. 30 minutes). There is also a lead fuse for additional protection. If this fuse blows, the interior heater must be sent to the factory for repair.

DEFA AS is conforming to the requirements of both ISO 9001:2008, ISO 14001:2004 and OHSAS 18001:2007. In addition to this, our engine heaters and cables are conforming to the requirements of ISO/TS 16949:2002.

Technical specifications

Voltage [V/Hz]	230 +/- 5%
Power [W] -25°C	0/1350*
Power [W] +20°C	0/1100
Rated power [W]	1350
Power start	1350
Fuse size [A]	10**
Operating temperature [°C]	-40 /+80
W/H/D [mm]	138/37/181
Weight [gram]	595
Bracket [gram]	20
IP rating	IP20
Insulation class	cl II
Certification	EN 60335-1 and EN 50408

* All power is stated at - 25°C

** The fuse size is based upon using the Termini™ together with a 600W engine heater.

Item number

DEFA no: #430050 (Incl. Termini™ plug for Termini™ extension cable #460860).

#430051 (Incl. Schuko plug).

12 - pack. (Weight: 7.5Kg)

Bracket no: #418070

Part of

Termini™ 1350 no. 430050 is a part of DEFA WarmUp no. 471250 and ComfortKit no. 470050.

Usage & mounting

The interior heater is mounted in the interior of the vehicle with special holders. Termini™ can be mounted upside down under the glove compartment, on the centre console or on the A-pillar according to the enclosed mounting instruction. Install the interior heater according to the enclosed installation guide.

www.defa.com

